

### AMENDMENTS TO THE CLAIMS

1. (currently amended) A line transition ~~including~~ comprising:  
a dielectric substrate;  
a ~~solid~~ waveguide, the waveguide propagating electromagnetic waves within a three-dimensional space; and  
a conductive pattern formed on the dielectric substrate, the conductive pattern including a coupled-line pattern segment electromagnetically coupled with the electromagnetic waves propagating through the waveguide and a transmission-line pattern segment extending from the coupled-line pattern segment ~~a planar circuit to realize planar-circuit to waveguide transition, the solid waveguide propagating electromagnetic waves within a three-dimensional space, the planar circuit being constructed by forming a predetermined conductive pattern on a dielectric substrate, wherein~~  
the dielectric substrate is disposed parallel to ~~the~~ an E plane of the ~~solid~~ waveguide ~~in almost the middle of the solid waveguide, and~~  
~~the conductive pattern on the dielectric substrate includes a coupled line pattern segment electromagnetically coupled with a signal propagating through the solid waveguide and a transmission line pattern segment extending from the coupled line pattern segment, and~~  
an ~~the~~ edge of the dielectric substrate has a notch in the vicinity of the coupled-line pattern segment, the notch having a side that is parallel to ~~a~~ the signal propagation direction of the coupled-line pattern segment, the length of the side being equal to or longer than ~~the dimension in the~~ a width ~~direction~~ of the E plane of the ~~solid~~ waveguide.
2. (original) A high frequency module including the line transition according to Claim 1.
3. (currently amended) A method for manufacturing a line transition including a ~~solid~~ waveguide and a planar circuit to realize planar-circuit to waveguide transition, the solid waveguide propagating electromagnetic waves within a three-dimensional space, the

planar circuit being constructed by forming a predetermined conductive pattern on a dielectric substrate, the dielectric substrate being disposed parallel to ~~an the~~ E plane of the solid waveguide in substantially a almost the middle of the solid waveguide, the conductive pattern on the dielectric substrate including a coupled-line pattern segment electromagnetically coupled with the electromagnetic waves a signal propagating through the solid waveguide and a transmission-line pattern segment extending from the coupled-line pattern segment, ~~an the~~ edge of the dielectric substrate having a notch in ~~a the~~ vicinity of the coupled-line pattern segment, the notch having a side that is parallel to ~~a the~~ signal propagation direction of the coupled-line pattern segment, ~~a the~~ length of the side being equal to or longer than ~~a the dimension in the width direction~~ of the E plane of the solid waveguide, the method comprising ~~the steps of~~:

forming a plurality of the conductive patterns in a ceramic green sheet;

forming and through holes in ~~[[a]]~~ the ceramic green sheet ~~serving as a~~ ~~motherboard~~ such that each through hole is arranged in ~~a the~~ vicinity of ~~a the~~ corresponding ~~line-coupled~~ coupled-line pattern segment of the conductive pattern at a predetermined spacing;

firing the ceramic green sheet to form a motherboard; and

cutting the ~~fired~~ motherboard along lines passing through the through holes such that each through hole in the ~~fired~~ motherboard serves as the notch.

4. (new) The line transition according to claim 1, wherein the waveguide is a solid waveguide.

5. (new) The line transition according to claim 1, wherein the conductive pattern is a planar circuit which accomplishes planar-circuit to waveguide transition.

6. (new) The line transition according to claim 1, wherein the dielectric substrate is disposed in substantially a middle of the waveguide.